



Platform scale in heavy version with EC type approval [M],  
now also up to [Max] 600 kg

## Features

- **Industrial quality:** because of its stable construction and robust design, it is ideal for continuous use in an industrial environment
- **Platform:** Weighing plate stainless steel, painted steel base, protection against dust and water splashes IP65, silicone-coated aluminium load cell, details see page 150
- **Display device:** Superior display size, digit height 52 mm for the easy reading of weighing results, even under poor lighting conditions. For details see page 147, KERN KFB-TM

- **Benchtop stand incl. wall mount**

for display device as standard

- **Level indicator and levelling feet** for precise levelling of the scale, fitted as standard, to give the most accurate weighing results

- **Weighing with tolerance range (checkweighing):** Input of an upper/lower limit value. A visual and audible signal assists with portioning, dispensing or grading

- **Totalising** of weights and piece counts

- **Hold function:** When the weighing conditions are unstable, a stable weight is calculated determining an average value

- **New:** high-resolution models for high-precision weighing and models with a weighing range of 600 kg!

# Industrial platform scale KERN IFB



E



1



2

## Technical data

- Large backlit LCD display, digit height 52 mm
- Weighing plate dimensions, stainless steel, WxDxH
  - A 300x240x110 mm
  - B 400x300x115 mm
  - C 500x400x137 mm, see enlarged picture
  - D 650x500x142 mm
  - E 800x600x200 mm
- Cable length of display device approx. 3 m
- Permissible ambient temperature  
-10 °C / 40 °C

## Accessories

- Protective working cover** over the display device standard. Can be re-ordered, scope of delivery: 5 items, KERN KFB-A02S05
- Signal lamp** for visual support of weighing with tolerance range. For details see page 181, can be retrofitted, KERN CFS-A03
- Stand** to elevate display device, **2** height of stand approx. 330 mm, see illustration, KERN IFB-A01 height of stand approx. 600 mm, can be retrofitted, for models with weighing plate size **C**, **D** and **E**, KERN IFB-A02 height of stand approx. 750 mm, can be retrofitted, KERN BFS-A07

- Y-cable**, RS-232, details see page 181, can be retrofitted, KERN CFS-A04
- Rechargeable battery pack internal**, operating time up to 35 h, charging time approx. 12 h, must be ordered at purchase, KERN KFB-A01
- Large display with superior display size**, for details see page 181, can be retrofitted, KERN YKD-A02
- Suitable printers** and further, extensive accessories from page 177 ff.

## STANDARD

--	--	--	--	--	--	--	--	--	--	--	--	--	--

only **E**

## OPTION

	+3 DAYS
--	---------

## FACTORY

--	--

only IFB-M only IFB-M

Model	Weighing range [Max] kg	Readout [d] g	Verification value [e] g	Minimum load [Min] g	Net weight approx. kg	Weighing plate		Options		
								Verification		DAKKS Calibr. Certificate
									KERN	DKD KERN
KERN								-	-	963-128
<b>IFB 6K-4</b>	6	0,2	-	-	6	<b>A</b>		-	-	963-128
<b>IFB 10K-4</b>	15	0,5	-	-	6	<b>A</b>		-	-	963-128
<b>IFB 10K-4L</b>	15	0,5	-	-	10	<b>B</b>		-	-	963-128
<b>IFB 30K-3</b>	30	1	-	-	10	<b>B</b>		-	-	963-128
<b>IFB 60K-3</b>	60	2	-	-	10	<b>B</b>		-	-	963-129
<b>IFB 60K-3L</b>	60	2	-	-	13	<b>C</b>		-	-	963-129
<b>IFB 100K-3</b>	150	5	-	-	13	<b>C</b>		-	-	963-129
<b>IFB 100K-3L</b>	150	5	-	-	22	<b>D</b>		-	-	963-129
<b>IFB 300K-2</b>	300	10	-	-	22	<b>D</b>		-	-	963-129
<b>IFB 600K-2</b>	600	20	-	-	51	<b>E</b>		-	-	963-130

Dual-range balance switches automatically to the next largest weighing range [Max] and readout [d].

<b>IFB 6K1DM</b>	3   6	1   2	1   2	20	6	<b>A</b>		965-228		963-128
<b>IFB 15K2DM</b>	6   15	2   5	2   5	40	6	<b>A</b>		965-228		963-128
<b>IFB 15K2DLM</b>	6   15	2   5	2   5	40	10	<b>B</b>		965-228		963-128
<b>IFB 30K5DM</b>	15   30	5   10	5   10	100	10	<b>B</b>		965-228		963-128
<b>IFB 60K10DM</b>	30   60	10   20	10   20	200	10	<b>B</b>		965-229		963-129
<b>IFB 60K10DLM</b>	30   60	10   20	10   20	200	13	<b>C</b>		965-229		963-129
<b>IFB 150K20DM</b>	60   150	20   50	20   50	400	13	<b>C</b>		965-229		963-129
<b>IFB 150K20DLM</b>	60   150	20   50	20   50	400	22	<b>D</b>		965-229		963-129
<b>IFB 300K50DM</b>	150   300	50   100	50   100	1000	22	<b>D</b>		965-229		963-129
<b>IFB 600K-1M</b>	300   600	100   200	100   200	2000	51	<b>E</b>		965-230		963-130

Note: For applications that require verification, please order verification at the same time, initial verification at a later date is not possible.  
Verification at the factory, we need to know the full address of the location of use.

# KERN Pictograms:

 <b>Internal adjusting:</b> Quick setting up of the balance's accuracy with internal adjusting weight (motordriven).	 <b>Piece counting:</b> Reference quantities selectable. Display can be switched from piece to weight.	 <b>Suspended weighing:</b> Load support with hook on the underside of the balance.
 <b>Adjusting program CAL:</b> For quick setting up of the balance's accuracy. External adjusting weight required.	 <b>Recipe level A:</b> Separate memory for the weight of the tare container and the recipe ingredients (net total).	 <b>Battery operation:</b> Ready for battery operation. The battery type is specified for each device.
 <b>Memory:</b> Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	 <b>Recipe level B:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display.	 <b>Rechargeable battery pack:</b> Rechargeable set.
 <b>Alibi memory:</b> Electronic archiving of weighing results, complying with the 2009/23/EC standard.	 <b>Recipe level C:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, adjustment of recipe when dosages are exceeded, multiplier function, barcode.	 <b>Universal mains adapter:</b> with universal input and optional input socket adapters for A) EU, GB B) EU, GB, CH, USA C) EU, GB, CH, USA, AUS
 <b>Data interface RS-232:</b> To connect the balance to a printer, PC or network.		 <b>Mains adapter:</b> 230V/50Hz in standard version for EU. On request GB, USA or AUS version available.
 <b>RS-485 data interface:</b> To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance.	 <b>Totalising level A:</b> The weights of similar items can be added together and the total can be printed out.	 <b>Power supply:</b> Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request.
 <b>USB data interface:</b> To connect the balance to a printer, PC or other peripherals.	 <b>Totalising level C:</b> Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, adjustment of recipe when dosages are exceeded, multiplier function, barcode recognition.	 <b>Weighing principle: Strain gauge</b> Electrical resistor on an elastic deforming body.
 <b>Bluetooth* data interface:</b> To transfer data from the balance to a printer, PC or other peripherals.		 <b>Weighing principle: Tuning fork</b> A resonating body is electromagnetically excited, causing it to oscillate.
 <b>WLAN data interface:</b> To transfer data from the balance to a printer, PC or other peripherals.	 <b>Percentage determination:</b> Determining the deviation in % from the target value (100 %).	 <b>Weighing principle: Electromagnetic force compensation</b> Coil inside a permanent magnet. For the most accurate weighings.
 <b>Control outputs (optocoupler, digital I/O):</b> To connect relays, signal lamps, valves, etc.	 <b>Weighing units:</b> Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details.	 <b>Weighing principle: Single cell technology</b> Advanced version of the force compensation principle with the highest level of precision.
 <b>Interface for second balance:</b> For direct connection of a second balance.	 <b>Weighing with tolerance range:</b> Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning.	 <b>Verification possible:</b> The time required for verification is specified in the pictogram.
 <b>Network interface:</b> For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter.	 <b>Hold function:</b> (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value.	 <b>DAkkS calibration possible (DKD):</b> The time required for DAkkS calibration is shown in days in the pictogram.
 <b>Wireless data transfer:</b> between the weighing unit and the evaluation unit using an integrated radio module.	 <b>Protection against dust and water splashes IPxx:</b> The type of protection is shown in the pictogram.	 <b>Package shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.
 <b>GLP/ISO log:</b> The balance displays the weight, date and time, regardless of a printer connection.	 <b>ATEX explosion protection:</b> Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device.	 <b>Pallet shipment:</b> The time required for internal shipping preparations is shown in days in the pictogram.
 <b>GLP/ISO log:</b> With weight, date and time. Only with KERN printers.	 <b>Stainless steel:</b> The balance is protected against corrosion.	 <b>Warranty:</b> The warranty period is shown in the pictogram.

## KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2000 kg. In combination with a DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe. Thanks to the high level of automation, we can carry out DAkkS calibration of

balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

### Range of services:

- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg – 2500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages D, GB, F, I, E, NL, PL